



The builders choice for quality- CoC certified



Hyne have ensured that our LVL is the most consistent and structurally superior LVL available in Australia. Engineers, architects, building designers and builders quickly recognised its quality and merits and see it as a valuable part of the Hyne ETP range.

Hyne LVL has many advantages over traditional building products, including uniformity of engineering properties, high strength to weight ratio, and availability in long lengths. Coming in 45mm and 63mm thicknesses with depths from 95mm to 360mm, Hyne LVL is

manufactured from plantation grown softwood and a maritime pine veneer is laminated in a continuous assembly with the grain direction of all veneers running lengthwise.

Hyne LVL can be used wherever sawn timber is used, but because it is a manufactured timber, available in long continuous lengths with high structural reliability, it is often used as: structural beams; floor joists and bearers; wall girts; lintel beams; roof framing or formwork bearers.

UNIFORM. HIGH STRENGTH. EFFICIENT.



Australian builders have been using LVL for many building applications including floor joists and bearers, lintels and verandah beams as well as structural roof members. This cost effective softwood is a strategic and efficient building component which can be integrated with other engineered timber products that make up the Hyne ETP range.

Engineers and building designers can specify Hyne LVL with confidence knowing that it conforms to the requirements of AS/NZS 4357 – Structural Laminated Veneer Lumber, with the design loads used to determine member sizes in Hyne Design based on AS 1684.1 1999 – Residential Timber Framed Construction.

For timber merchants and frame and truss manufacturers, Hyne LVL is available ex-stock from Hyne Wholesale either as part of a job lot order or in full pack lots. This flexible supply arrangement allows Hyne customers to choose the way that best suits them.

SIZES

45mm x depths in mm*	95, 130, 150, 170, 200, 245, 300, 360
63mm x depths in mm*	95, 130, 150, 170, 200, 245, 300, 360

* Please be advised that not all sizes and depths available in all regions. Please contact your nearest Hyne Wholesale for Stock Ranges and availability.

LENGTHS

45mm Lengths (m) 3.0 to 8.4 in 0.3 increments
then 9.0m, 9.6m, 10.2m and 12.0m

63mm Lengths (m) 3.0 to 6.0 in 0.3 increments
then 6.6m to 12.0m in 0.6 increments

GRADES

Hyne LVL is available in structural grade only

